



[Home](#) > [News & Information Resources](#) > [Intellectual Property Digital Library](#)

[Images](#) [Description and Claims \(117 Kb\)](#)

Welcome

PCT (Patents)

Trademarks

Designs

Article 6ter

Resources

[[printable version](#)]

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION (PCT)

(11) WO 02/073646

(13) A2

(21) PCT/GB02/00962

(22) 11 March 2002 (11.03.2002)

(25) English

(26) English

(30) 0106358.5

13 March 2001
(13.03.2001)

GB

(43) 19 September 2002 (19.09.2002)

(51)⁷ H01J 1/00

(54) FIELD ELECTRON EMISSION MATERIALS AND DEVICES

(71) PRINTABLE FIELD EMITTERS LIMITED [GB/GB]; Atlas Centre, Rutherford Appleton Laboratory, Chilton, DIDCOT, Oxfordshire OX11 0QX (GB).

(72) BURDEN, Adrian, Paul [GB/GB]; 36 Crafts End, Chilton, Didcot, Oxfordshire OX11 0SA

(75) BAIGRIE, Stephen, Michael [GB/GB]; 104 Ridge Nethermoor, Liden, Swindon, Wiltshire SN6 6NE (GB).

(74) STANLEY, David, William; Stanleys, Kings Court, 12 King Street, Leeds, Yorkshire LS1 4JL (GB).

(81) AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, D, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZM,


(84) ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, ML, MR, NE, SN, TD, TG)

[For information on time limits for entry into the national phase please click here](#)

Published

— without international search report and to be republished upon receipt of that report

(57) Graphite comprises atoms arranged in discrete layers (100). The perpendicular distance between these layers is the 'd-spacing' (101). A field emission material is obtained by expanding the d-spacing (102). Such expansion may be achieved by an intercalant that has been introduced between layers of the material. Such an intercalant may reside, or may no longer reside, in the material. The material may be placed in position on a substrate by a printing process, prior to expansion. Such field emission material may be used as cathodes in field electron emission devices.



Terms of use